

A

1c525 U.S. PTO
01/15/99

jc526 U.S. PTO
09/232289
01/15/99

6	7	8	9
10	11	12	13
14	15	16	17
18	19	20	21
22	23	24	25
26	27	28	29
30	31	32	33
34	35	36	37
38	39	40	41
42	43	44	45
46	47	48	49
50	51	52	53
54	55	56	57
58	59	60	61
62	63	64	65
66	67	68	69
70	71	72	73
74	75	76	77
78	79	80	81
82	83	84	85
86	87	88	89
90	91	92	93
94	95	96	97
98	99	100	101
102	103	104	105
106	107	108	109
110	111	112	113
114	115	116	117
118	119	120	121
122	123	124	125
126	127	128	129
130	131	132	133
134	135	136	137
138	139	140	141
142	143	144	145
146	147	148	149
150	151	152	153
154	155	156	157
158	159	160	161
162	163	164	165
166	167	168	169
170	171	172	173
174	175	176	177
178	179	180	181
182	183	184	185
186	187	188	189
190	191	192	193
194	195	196	197
198	199	200	201
202	203	204	205
206	207	208	209
210	211	212	213
214	215	216	217
218	219	220	221
222	223	224	225
226	227	228	229
230	231	232	233
234	235	236	237
238	239	240	241
242	243	244	245
246	247	248	249
250	251	252	253
254	255	256	257
258	259	260	261
262	263	264	265
266	267	268	269
270	271	272	273
274	275	276	277
278	279	280	281
282	283	284	285
286	287	288	289
290	291	292	293
294	295	296	297
298	299	300	301
302	303	304	305
306	307	308	309
310	311	312	313
314	315	316	317
318	319	320	321
322	323	324	325
326	327	328	329
330	331	332	333
334	335	336	337
338	339	340	341
342	343	344	345
346	347	348	349
350	351	352	353
354	355	356	357
358	359	360	361
362	363	364	365
366	367	368	369
370	371	372	373
374	375	376	377
378	379	380	381
382	383	384	385
386	387	388	389
390	391	392	393
394	395	396	397
398	399	400	401
402	403	404	405
406	407	408	409
410	411	412	413
414	415	416	417
418	419	420	421
422	423	424	425
426	427	428	429
430	431	432	433
434	435	436	437
438	439	440	441
442	443	444	445
446	447	448	449
450	451	452	453
454	455	456	457
458			

of pending prior application:
Serial No.: 09/022,289
Filed: February 11, 1998
Prior Examiner: Unknown
Prior Group: 2733

Box Application
To The Assistant Commissioner
for Patents
Washington, D.C. 20231

Dear Sir:

- IPDAL.191367.1 34650-00250USPT

1A. Always X one box, only:

X 1a. Newly executed oath or declaration (original or copy) of 3 pages.
 _____ 1b. A signed declaration or oath as originally filed in prior application attached.
 Number of pages _____

_____ a. This application is filed by less than all of the inventors named in the prior application. Petition is hereby made requesting deletion as inventor(s) of the following who is/are not inventor(s) of the invention being claimed in this application:

1. _____ 2. _____
 3. _____ 4. _____

X 1c. Incorporation by reference:
 The entire disclosure of the prior application, from which a copy of the oath or declaration is being supplied under Box 1b is considered as being a part of the disclosure of the accompanying application and is hereby incorporated by reference therein.

_____ 1d. A declaration is not being supplied at this time. A declaration will be executed in due course and forwarded in accordance with 37 CFR 1.53(b) and 37 CFR 1.53(f).

_____ 2. Transfer the drawings from the prior application to this application and abandon said prior application as of the filing date accorded this application. A third copy of this letter is attached for filing in the prior application file.

_____ 3. Priority is claimed under 35 U.S.C. 119/365 based on filing in _____ (country) of

<u>Application No.</u>	<u>Filing Date</u>	<u>Application No.</u>	<u>Filing Date</u>
(1) _____	_____	(4) _____	_____
(2) _____	_____	(5) _____	_____
(3) _____	_____	(6) _____	_____

_____ a. _____ (No.) Certified copy/copies attached.
 _____ b. Certified copy/copies previously filed on _____ in U.S. Application No. _____, filed on _____.
 _____ c. Certified copy/copies filed during International stage of PCT/_____.
 _____ d. Priority is also claimed from PCT/_____ filed _____.

☒ 4. Prior application is assigned to Telefonaktiebolaget L M Ericsson by means of an Assignment recorded on May 12, 1998 at Reel 9161, Frame 0319.

☐ 5. Attached is an Assignment and Cover Sheet. Please return the recorded Assignment to the undersigned.
(NOTE: add assignment filing fee below.)

☒ 6. The power of attorney in the prior application is to at least:
The address of whom is in item 8.

☐ THOMAS E. ANDERSON Reg. No. 37,063
☐ JEFFERY E. BACON Reg. No. 35,055
☐ MICHAEL J. BALCONI-LAMICA Reg. No. 34,291
☐ THOMAS L. CANTRELL Reg. No. 20,849
☒ THOMAS L. CRISMAN Reg. No. 24,846
☐ STUART D. DWORK Reg. No. 31,103
☐ H. MATHEWS GARLAND Reg. No. 19,129
☒ J. KEVIN GRAY Reg. No. 37,141
☐ STEVEN R. GREENFIELD Reg. No. 38,166
☐ KEVIN R. HANSBRO Reg. No. 38,485
☐ J. PAT HEPTIG Reg. No. 40,643
☐ CRAIG A. HOERSTEN Reg. No. 38,917
☐ JOHN R. KIRK JR. Reg. No. 24,477
☐ PETER J. MANSO Reg. No. 32,264
☒ ROGER L. MAXWELL Reg. No. 31,855
☐ ROBERT A. McFALL Reg. No. 28,968
☐ LISA H. MEYERHOFF Reg. No. 36,869
☒ STANLEY R. MOORE Reg. No. 26,958
☐ RICHARD J. MOURA Reg. No. 34,883
☐ MARK V. MULLER Reg. No. 37,509
☐ P. WESTON MUSSELMAN JR. Reg. No. 31,644
☐ RICHARD A. MYSLIWIEC Reg. No. 40,098
☐ KEITH W. SAUNDERS Reg. No. 41,462
☐ JERRY R. SELINGER Reg. No. 26,582
☐ SCOTT STAHL Reg. No. 33,795
☐ RICHARD J. STOKEY Reg. No. 40,383
☒ ANDRE M. SZUWALSKI Reg. No. 35,701
☐ ALAN R. THIELE Reg. No. 30,694
☐ WILLIAM J. TUCKER Reg. No. 41,356
☐ CHARLES PATRICK TURLEY Reg. No. 35,723
☐ TAMSEN VALOIR Reg. No. 41,417
☒ RAYMOND VAN DYKE Reg. No. 34,746
☒ BRIAN D. WALKER Reg. No. 37,751
☒ GERALD T. WELCH Reg. No. 30,332
☐ Other: _____

- ____ 7.a. Recognize _____, Reg. No. _____ as having associate power of attorney.
(Name and Reg. No.; Address as in item 8 unless otherwise indicated)
- ____ 7.b. _____ Reg. No. _____ was recognized as associate power of attorney in the parent application.
- ____ 7.c. Since a power does not appear in the original papers, a copy of the power in the prior application is attached.
8. Address all future communications to:
- Raymond Van Dyke, Esq.
Jenkins & Gilchrist, P.C.
1445 Ross Avenue, Suite 3200
Dallas, Texas 75202
- X 9. Amend the specification by inserting before the first line of the application the sentence: -- This application is a _____ continuation _____ division X continuation-in-part of Application No. 09/022,289, filed February 11, 1998.--
- ____ 10. _____ (No.) Verified Statement(s) establishing "small entity" status under Rules 9 & 27
____ have been filed in above prior application (and is still be beleived to be proper and desired)
____ are attached hereto.
- X 11. **PETITION to extend the life** of the above prior application to at least the date hereof.
(One box must be X'd)
____ is being concurrently filed in that prior application.
____ was previously filed in that prior application (Check length of prior extension).
 X is not necessary for copendency (**Double check** before X'ing this box).
- X 12. **INFORMATION DISCLOSURE STATEMENT:** Attached is Form PTO-1449 listing newly cited documents not cited by Applicant or the PTO in the parent application(s) relied upon under 35 U.S.C. 120 and referenced above. Per Rule 98(d) copies of those documents are not required now. Please fully consider those documents and advise that they have been considered in this new application as by returning a copy of the enclosed Form PTO-1449 with the Examiner's initials in the left column per MPEP 609.

- ____ 13. Attached is a Rule 103(a) Petition to Suspend Action.
- ____ 14. The following Filing Fee calculation is based on the claims filed.

NOTE: If box 1D is X'd, do not pay any fees at this time

					SMALL ENTITY RATE			LARGE ENTITY RATE		
BASIC FEE			<u>Design</u> Appln.		\$155	<u>OR</u>		\$310	=	\$ ____
BASIC FEE			<u>Utility</u> Appln.		\$380	<u>OR</u>		\$760	=	\$ <u>760.00</u>
	NUMBER FILED			NUMBER EXTRA						
TOTAL CLAIMS	<u>35</u>	-20	=	<u>15</u> (at least 0)	x 9	<u>OR</u>	x 18	=		+ \$ <u>270.00</u>
INDEP. CLAIMS	<u>3</u>	- 3	=	<u> </u> (at least 0)	x 39	<u>OR</u>	x 78	=		+ \$ <u>0</u>
If any <u>proper</u> multiple dependent claim (ignore improper) is present					+\$130	<u>OR</u>	+\$260	=		+ \$ ____
If assignment is x'ed (Item 5)..... add recording fee (\$40 00)										+ \$ ____
If "petition" Item 11 above is X'dadd petition fee (\$130.00)										+ \$ ____
TOTAL FILING FEE					=					\$ <u>1,030.00</u>


- X 15. ATTACHED: (other)
acknowledgment postcard
- X 16. A check in the amount of \$ 1,030.00 to cover the TOTAL FEE is attached. Please charge any deficiency or credit any overpayment to Deposit Account No. 10-0447.
- ____ 17. Please charge Jenkins & Gilchrist's Deposit Account No. 10-0447 in the amount of \$ ____ to cover the TOTAL FEE. This sheet is attached in duplicate.

CHARGE STATEMENT: The Commissioner is hereby authorized to charge any fee specifically authorized hereafter, or any missing or insufficient fee(s) filed, or asserted to be filed, or which should have been filed herewith or concerning any paper filed hereafter, and might be required to make any response or reply timely or may be required under 37 CFR 1.16-1.18 (missing or insufficiencies only) now or hereafter relative to this application and for the resulting Official Document under 37 CFR 1.20, OR credit any overpayment to our Deposit Account No. 10-0447, for which purpose a duplicate copy of this sheet is attached.

This CHARGE STATEMENT does not authorize charge of the issue fee until/unless an issue fee transmittal form is filed.

Respectfully submitted,

JENKENS & GILCHRIST, P.C.

By: 
Raymond Van Dyke
Registration No. 34, 746

Dated: January 15, 1999

JENKENS & GILCHRIST, P.C.
1445 Ross Avenue, Suite 3200
Dallas, Texas 75202
Tel: 214/855-4708
Fax: 214/855-4300

NOTE: File this Request in duplicate with a return postcard and attachments or in triplicate if item 3 is marked.

CERTIFICATE OF MAILING BY EXPRESS MAIL

"EXPRESS MAIL" Mailing Label No. EL063369769US
Date of Deposit: January 15, 1999
I hereby certify that this paper or fee is being
deposited with the U.S. Postal Service "Express Mail
Post Office to Addressee" service under 37 C.F.R.
1.10 on the date indicated above and is addressed to
the Assistant Commissioner for Patents, Box Patent
Application, Washington, D.C. 20231

Type or Print Name: Carol Marsteller

Signature

**SYSTEM, METHOD AND APPARATUS FOR SECURE TRANSMISSION
OF CONFIDENTIAL INFORMATION**

CROSS REFERENCE TO RELATED APPLICATIONS

This application is a continuation-in-part of Assignee's
U.S. Patent Application Serial No. 09/022,289, entitled
"System, Method and Apparatus for Secure Transmission of
Confidential Information", filed on February 11, 1998, and
incorporates by reference Assignee's co-pending U.S. Patent
Application Serial No. 08/845,938, entitled "Combined Mobile
Telephone and Remote Control Terminal", filed on April 29,
1997.

BACKGROUND OF THE PRESENT INVENTION

Field of the Invention

The present invention relates generally to a system, method and apparatus for establishing a secure wireless communications link between two devices that minimizes the risk of third party interception of sensitive information, such as may be exchanged during communication initialization.

Background and Objects of the Present Invention

The evolution of wireless communication over the past century, since Guglielmo Marconi's 1897 demonstration of radio's ability to provide continuous contact with ships sailing the English Channel, has been remarkable. Since Marconi's discovery, new wireline and wireless communication methods, services and standards have been adopted by people throughout the world. This evolution has been accelerating, particularly over the least ten years, during which the mobile radio communications industry has grown by orders of magnitude, fueled by numerous technological advances that have made portable radio equipment smaller, cheaper and more reliable. The exponential growth of mobile telephony will continue to rise in the coming decades as well, as this

wireless network interacts with and eventually overtakes the existing wireline networks.

Cordless telephony has also been a part of the exponential rise in wireless telephony. Cordless telephones were originally aimed at providing economical, tetherless voice communications inside residences, i.e., using a short wireless link to replace the cord between a telephone base unit and its handset. Although early cordless phones were of marginal quality, with the introduction of improved cordless phones in the 1980s sales dramatically increased. More recent advances, particularly in Europe, have extended the use domain of cordless phones outside of residences.

Another European revolution of cordless telephones is the digital enhanced cordless communications (DECT) standard, which was optimized for use inside buildings. DECT controllers may hand off active calls from one base unit to another as the users move, and can page or ring handsets as a user walks through areas covered by different base units. As is understood in the art, however, the range of cordless telephones is greatly limited compared to the more versatile cellular telephones, i.e., 0.3-30 or more kilometer range for cellular and less than 100 meters in cordless systems, and usually only up to tens of meters.

More recently, the worlds of cellular and cordless telephony have begun to converge with the introduction of cordless standards compatible with that of its cellular cousin. Accordingly, a mobile cellular user may utilize their cellular telephones within a cordless telephony system, thereby avoiding the need to purchase proprietary and typically non-compatible cordless telephones. Shown in FIGURE 1 is a private telephone system, generally referred to by the numeral 10, having at least one private base station 12 and a multiplicity of cellular phones 14 in communication therewith. When in a cordless mode a cellular user, e.g., at phone 14A, may communicate with another user within the private telephone system 10, e.g., another cordless-mode cellular phone 14B or a cordless phone 16, via the private base station 12 which serves as a relay.

One problem with the use of the cellular phones 14 within the private telephone system 10 is security. As discussed, original cordless telephones, e.g., phones 16 in FIGURE 1 were stand-alone consumer products that did not require any interoperability specifications. In other words, each cordless phone came with its own base station and needed to be compatible only with that base station. Billing, security and privacy concerns within such systems were

addressed by both preventing that cordless phone from
operating with any other base station and limiting the
transmission range of the cordless phones. With the
convergence of cordless and cellular technologies and the use
5 of interoperability specifications, however, the inherent
physical limitations of the cordless systems no longer serve
a security function. With cellular phones 14 being capable
of transmitting their signals over many kilometers, the use
of such phones within private telephone systems 10 raise
10 genuine security considerations.

As is understood in the art, cellular phone 14A may
communicate through the private base station 12 by use of
encryption keys or other such security protocol, whereby the
messages are encrypted and more difficult to decipher.
15 Accordingly, even though the communications from a cellular
user communicating within the private telephone system 10 may
extend well outside the outer reaches of the system 10, the
conversation or data exchanged is kept relatively confiden-
tial. Another problem, however, arises during communication
20 initialization over the radio interface which must occur
without encryption since no encryption keys have been
exchanged between the cellular user, e.g., of cellular
terminal 14A. The information is therefore being broadcast

across a wide range, including the keys, until encryption protocols are established. Accordingly, third parties may listen in on such pre-encryption transmissions and acquire sensitive information.

5 Various techniques may be employed to thwart such eavesdropping. A first approach is to use a wireline connection for the initial information exchange, whereby the cellular phone 14A must be electrically connected to the private base station to start the private communication.
10 This approach would, accordingly, require the definition of an electrical interface between the two components and limit the manufacturer's freedom to design attractive terminals since a standardized connector may increase the size and weight of the terminal. Further, such a definition may also
15 restrict further improvements of such phones 14, e.g., moving to lower voltage technologies for energy conservation and size deduction.

 An alternative approach would be using Subscriber Identity Modules (SIMs) in both the private base station
20 and the respective cellular terminal 14, whereby the requisite identification information is readily established and the proper keys applied without transmitting them. In addition to the added component costs, the use of two SIMs

in this manner also adds to the administrative costs of mobile network operators who must allocate unique SIM pairings between the private base stations 20 and respective cellular terminals 14. Furthermore, there is a risk that a
5 SIM meant for the cellular terminal 14 may instead be inserted into the private base station 12, further complicating this approach.

A third approach is to utilize the advantages of the radio interface, e.g., standardization. As discussed,
10 however, because radio waves propagate through walls and over large distances, this also poses a security risk which must be overcome.

In view of the disadvantages of each of the aforementioned approaches, it is clear that there is a need
15 for a simple and secure system and method for establishing a communications link between a first device, such as a cellular phone, and another device, such as a private base station.

It is, accordingly, an object of the present invention
20 to provide a system, method and apparatus for establishing such a simple and secure communications link, whereby at least a portion of a transmission, particularly one containing sensitive information, may be transmitted clearly

for proper reception while simultaneously minimizing the risk of interception.

It is a further object of the present invention to provide additional systems, methods and apparatuses that
5 securely transmit confidential or sensitive information for establishing a connection between a first and a second device that communicate via radio links, e.g., a lap-top computer and a peripheral device such as a printer.

It is another object of the present invention to provide
10 a secure wireless transmission link between any two devices, whether in the work-place or at home, e.g., a computer which receives an Internet command to turn on the heat in an apartment. After the establishment of the secure link, using the systems, methods and apparatuses of the present
15 invention, the two devices may then communicate via short- or long-range wireless radio links without the need for proprietary cables or other physical interconnection.

SUMMARY OF THE INVENTION

The present invention is directed to a system, method and apparatus for establishing a secure wireless radio communications link between two devices that minimizes the exposure of sensitive information to third party interception. The secure link is established by establishing an infrared link between the two devices for the exchange of sensitive information, such as encryption information. Subsequent communications would then have the benefit of encryption protection, establishing the secure wireless radio communications link.

A more complete appreciation of the present invention and the scope thereof can be obtained from the accompanying drawings which are briefly summarized below, the following detailed description of the presently-preferred embodiments of the invention, and the appended claims.

BRIEF DESCRIPTION OF THE DRAWINGS

FIGURE 1 is a schematic illustration of a private telephone system, including a private base station with cellular and cordless phones in communication therewith;

FIGURE 2 illustrates a dual-mode radiofrequency and infrared mobile station and private base station in accordance with the present invention;

FIGURE 3 illustrates various circuitry employed in the dual-mode devices shown in FIGURE 2; and

FIGURE 4 illustrates a variety of devices that communicate with each other using the principles of the present invention.

DETAILED DESCRIPTION OF THE PRESENTLY PREFERRED EXEMPLARY EMBODIMENTS

The present invention will now be described more fully hereinafter with reference to the accompanying drawings, in which preferred embodiments of the invention are shown. This invention may, however, be embodied in many different forms and should not be construed as limited to the embodiments set forth herein; rather, these embodiments are provided so that this disclosure will be thorough and complete, and will fully convey the scope of the invention to those skilled in the art.

The use of infrared (IR) transmissions between diverse electronic devices, e.g., between a television and a remote controller, are known, e.g., U.S. Patent Nos. 5,508,836,

5,588,009, 5,564,020, 5,617,236 and 5,446,783 each describe various IR-electronic interconnections. U.S. Patent No. 5,636,264 similarly describes an IR interface between a phone handset and a computer. Although generally describing the usage of IR in these contexts, the references fail to discuss the aforementioned security problems inherent in wireless communications nor the proposed solution set forth in the present invention, described in more detail hereinafter.

Shown in FIGURE 2 is a dual mode mobile station 20 in communication with a dual mode private base station 21. As discussed, mobile station 20 communicates with the private base station 21 via an RF transmission, which has an effective range of hundreds of meters, and via a more limited, "cordless" communications mode having a much shorter, contained range. As is understood in the art, the RF transmission mode is via the respective antennae 20A and 21A of the mobile station 20 and private base station 21, respectively, the signals being transceived in a conventional manner.

Also shown in FIGURE 2 are IR transceiver interfaces 20B and 21B on the mobile station 20 and private base station 21, respectively. Each interface preferably includes a photodetector 22 for receiving IR signals and an IR signal

emitter 23 for transmitting such IR signals. It should be understood that the position of the interfaces 20B and 21B on the respective bodies of the mobile station 20 and the private base station 21 are arbitrary, provided the
5 respective IR signals to and from the interfaces 20B and 21B are not blocked, e.g., by the palm or fingers of the phone user. In other words, ergonomic considerations may dictate particular placements for the interfaces, as is understood in the art.

10 With further reference to FIGURE 2, one of the practical utilizations of the dual-mode mobile station 20 is now illustrated. In particular, when the dual-mode mobile station 20 comes within the more limited range of the private base station 21, e.g., in the same or an adjacent room, the
15 subscriber may wish to transfer control from the cellular provider to the private system, e.g., to save money on the cheaper wireline phone rates through the private system to the Public Switched Telephone Network (PSTN). For example, through the PSTN 24, the mobile station 20 can communicate
20 with remote wireline phones 25 and remote cellular phones 26 via a base transceiver system 27 (shown for simplicity as a base transceiver station tower).

With reference now to FIGURE 3 of the drawings, there is illustrated a portion of the mobile station 20 (in FIGURE 2), particularly, the IR transceiver interface 20B and various circuitry within the mobile station 20 for handling the IR signals. An IR receiver or photodetector 30 receives the IR signals, such as from the private base station 21, and passes the signals to a decoder 31, which converts the infrared information within the IR signal to electrical information, e.g., digital pulses. The converted information is then forwarded to a controller 32, which controls the flow of the electrical information (pulses). A signal conversion device 33 receives the aforesaid electrical information flow and groups the incoming pulses into a unit size (frame) pursuant to a known signal format. The controller 32 may be a UART or other like controller, as is understood in the art.

The incoming signal, now translated, is sent to a processor 34, which implements the command(s) set forth in the signal, e.g., forward the incoming signal to another phone such as mobile station 14B (in FIGURE 1) across the RF communications link. Similarly, the processor 34, in response to one or more commands, may send a message across the IR communications link by first forwarding the message to the signal conversion device 33, which converts the

structured message into the aforesaid electrical information or pulses, which the controller 32 sends to an encoder 35. The electrical pulses are there converted to IR radiation signals which are then transmitted by an IR transmitter 36, e.g., light emitting diodes, releasing the IR signal.

It should, of course, be understood that the circuitry shown in FIGURE 3 is preferably also incorporated within the private base station 21 so that a wireless IR dialogue may be established with the mobile station 20.

As discussed, the effective range of the IR signal so emitted is limited, e.g., on the order of several dozens of meters. With obstacles like walls, floors and ceilings, the effective range is even further reduced, as is encountered by consumers with products such as television remotes. Accordingly, IR signals provide an excellent way to exchange confidential information wirelessly, effectively limiting communications to a point-to-point conversation, albeit preferably temporarily until the security protocols are safely established. Eavesdropping, although still possible, is thwarted by such range restrictions since other security measures, e.g., building control, may be employed in conjunction to provide almost any level of interception prevention.

Since various encryption methods are available to make a wireless conversation almost impervious to code-breakers, wireless communications between a user of the dual-mode phone 20 (in FIGURES 2 and 3) preferably switches to the RF communications mode to utilize the enhanced security advantages of encryption to prevent deciphering. Wireless RF communications, however, even with encryption, are easily intercepted by a distant eavesdropper. Although encryption data may thwart the eavesdropper's deciphering the intercepted coded message, the caller and recipient must first establish the secure transmission through the exchange of encryption keys over a non-encrypted wireless communication, which the eavesdropper can monitor, easily decipher the pertinent keys and then decipher the supposedly secure encrypted transmissions.

The system, method and apparatus of the present invention provide an improved, more secure way to preserve the confidentiality of wirelessly transmitted information by restricting exposure of the encryption keys and any other confidential information through use of the aforementioned IR transmissions.

In one embodiment of the present invention the subscriber of mobile station 20 when sufficiently close to

the private telephone system, e.g., near the private base station 21, activates the mobile station 20 to emit an IR signal, e.g., via IR transmitter 36. Alternatively, the mobile station 20 may activate IR signaling capability automatically in advance of transceiving any security-related data. In a preferred embodiment of the present invention, the mobile station utilizes conventional radiofrequencies for all non-security-related transmissions, e.g., when initiating communications with the private base station 21 such as a cordless telephone base station and after the exchange of encryption or other such security data. Upon reaching the aforementioned security data or protocols in the transmission, the mobile station 20 then switches over to the aforementioned IR signaling using the IR transmitter 36. It should be understood, that the RF-to-IR switchover may occur early in the transmission, e.g., in the initial communications attempts, or later during the transmission, so long as any secured portions of the signal are transmitted via IR transmissions.

In either event, the private base station 21 detects the IR signal transmission from the mobile station 20, via the aforementioned photodetector 30 in the station 21, processes the incoming IR signal, and responds with an IR response

signal, which preferably includes an encryption key. It should be understood that one or more encryption keys may be inserted into the response signal by an encryption device 37 in communication with the processor 34. Upon the secure receipt of the encryption key(s) from the private base station 21 via IR transmission, the mobile station 20 may then safely begin/resume wireless RF communications, which are now encrypted pursuant to the embedded encryption key(s). The subscriber is then able to move more freely throughout the building, all the while taking advantage of the inexpensive wireline communications link through the PSTN 24, as discussed hereinbefore.

In another embodiment of the present invention, the private base station 21 may periodically emit an IR signal, which the mobile station 20 may intercept, if close enough. In effect, the private base station may perform an IR poll to establish the preliminary IR linkage to exchange security information, such as the aforescribed encryption keys. For example, upon detection (in photodetector 30), the mobile station 20 may (like the private base station 21 in the previous embodiment) also respond with an IR response signal, which may include encryption key(s) for governing the subsequent RF transmissions with the private base station 21,

thereby providing a procedure for periodic or random security measures.

In still another embodiment of the present invention, the more secure IR communications link may be employed by the subscriber of the mobile station 20 or an administrator of the private telephone system to transfer other, non-initialization-related information. For example, if particularly sensitive information needs to be transmitted during an RF communication, the mobile station 20 and private base station 21 may switch to the more private IR communications mode and resume the RF mode transmissions after the sensitive information has been transferred. It should also be understood that the mobile station 20 and private base station 21 may automatically revert to the IR communication mode while in range of each other and only switch over when the IR transmissions begin to deteriorate.

Although one preferred embodiment of the present invention utilizes the principles of the present invention in the context of mobile telephony, it should be understood that the scope of the present invention, as set forth in the claims hereinbelow, covers a variety of dual-mode wireless interconnections using an infrared mode for security purposes.

With reference now to FIGURE 4, there is illustrated a further embodiment of the present invention in which a first device, such as a mobile phone, a headset on a user or a computer, communicates with at least one of a large number of other devices, such as set forth in detail in Assignee's pending patent application entitled "Combined Mobile Telephone and Remote Control Terminal", U.S. Patent Application Serial No. 08/845,938, filed April 29, 1997, incorporated herein in its entirety by reference. It should be understood that although all of the various devices depicted in FIGURE 4 may be able to communicate with each other, certain pairings may not be utilized (at present). For example, a printer 50 (receiving commands from a personal computer or PC 48) need not communicate with a television 68, although the television 68 could transmit an image for printing at the printer 50. The printer 50, however, could well forward a printing completion message (or out-of-paper or error message) to the PC 48 (using the security measures of the instant application or not).

Recent initiatives, such as the Bluetooth Mobile Communications Initiative, are promoting the increase in interoperability of the various electrical, electronic and mechanical devices utilized in the work place and at home.

A number of the various devices capable of using the Bluetooth or other like technology are illustrated in FIGURE 4, including a home base station 40 which is linked to a conventional Public Switched Telephone Network (PSTN) 42, converting the wireless rf and infrared signals received from other devices, such as the dual-mode phones 26 (shown in FIGURE 2), a wireless headset/hands-free unit 44 or other cordless device 46. The desk-top or lap-top PC 48 may also interact with a number of additional peripheral devices, e.g., printer/plotter/projector 50, a facsimile 52, a pager 54, a data organizer 56 or other such personal, hand-held organizer device (enabling the download of sensitive information both to and from the organizer 56 and synchronization with data stored in the PC 48, another PC 57 or an electronic data terminal 58), a scanner 60, microphone 62, a PC card 64 and numerous other such peripherals, generally designated by the reference numeral 66. Of course, the principles of the present invention are also applicable in the mobile station 26 and a SIM card 26A, such as the one associated therewith, or a SIM card 67 separate from mobile station 26 as illustrated in FIGURE 4.

In the home, numerous other household devices may be equipped with the dual-mode functionality such as set forth

in the present invention. For example, the PC 48 may intercommunicate with the television 68, a radio 70, a stereo 72 or peripheral attached thereto, or a VCR or other video player 74 (tape or disk). Other interconnected devices in the home include a light device (lamp) 76, a dimmer switch 78, a thermostat 80 to control heating/cooling of a domicile, a door device 82 such as a garage door, a refrigerator/freezer 84, a cooking device 85 (microwave, gas, etc.), a washer/dryer 86, an answering machine 88 and an alarm device 90. Additional devices that may include the inventive techniques of the present invention include a car alarm 92 (with a car lock feature), which to operate in infrared mode must be in close proximity, preferably also in line-of-sight, and other external alarm devices which may be stationary.

Utilizing the principles of the present invention, secure communications may be established, via the infrared and wireless links, enabling a user, e.g., through voice or keyed-entry commands entered into a handheld or wrist (watch) communication device, generally designated by the reference numeral 94, to open their garage door 82, exit and lock their car, disarm their home alarm devices 90, and enter their domicile which has been heated/cooled by a prior remote

command to the thermostat 80 (relayed wirelessly by the home PC 48).

It should be understood that although the plethora of wirelessly interconnected devices, such as specified pursuant to the Bluetooth initiative, may utilize low-cost, short-range radio links instead of the expensive, cumbersome and proprietary cabling now required, the need for securing these rf transmissions, which may range for a hundred meters or more, is critical since an unauthorized user could easily eavesdrop, intercept and decrypt these communications, thereby gaining access to the personal domain and effects of a user. The initial, more secured infrared transmissions of the present invention, requiring close proximity, more line-of-sight security data exchanges, provide the requisite level of protection necessary in these open-to-tampering systems.

Frequency spectrums available for these private applications are, at present, rather limited. In the United States, for instance, bands at 900 MHZ, 2.4 GHz and 5.7 GHz are currently unlicensed and may be used freely, provided the transmission (TX) power levels are low or spreading is applied. The Bluetooth initiative is scheduled to operate at the globally-available 2.45 GHz Industrial, Scientific, Medical (ISM) 'free band', allowing international travelers

to employ Bluetooth-enabled equipment worldwide. It is understood to those skilled in the art that in an effort to avoid interference, spreading should be applied either by Frequency Hopping (FH) or direct-sequence (DS) spread spectrum. The 2.45 GHz ISM band may be used for a variety of devices and constitutes a band ranging from about 2.4 GHz to about 2.483 GHz, as described in Assignee's co-pending patent application entitled "Method and Apparatus for Tracking a Mobile Phone". As discussed in said patent application, describing frequencies in a phone tracking system, in an effort to avoid sharp filters to fulfill out-of-band emission requirements, the applied radio band is preferably placed away from the ISM band edges. Known interference areas, e.g., from 2.435 GHz to 2.465 GHz in which microwave ovens operate, are preferably avoided as well. Frequency Shift Keying (FSK) can be used to map the user code on the rf carrier. In such an FSK modulation technique, a bit representing 'one' is mapped to the frequency $rf + Df$, and a bit representing 'zero' is mapped to the frequency $rf - Df$ (or vice versa) where rf is the carrier frequency and Df is the frequency deviation, which should be large enough to combat the frequency offset between the transmitter and the receiver. For example, if inaccurate

frequency references (with an accuracy of about 50 parts per million) are used, the worst-case frequency offset can reach up to 240 KHz. In order to receive the burst in such a case, the frequency duration D_f should be greater than 240 KHz.

5 It should be understood that although GSM technology is presently preferred, the principles of the present invention may also be employed in other Time Division Multiple Access (TDMA), Personal Digital Cellular (PDC) and presently developed (and future) third generation systems and
10 equipment. Consequently, the various frequencies used by these and other systems, e.g., 800, 900, 1500, 1800, 1900, 2000 and 2100 MHz bands, may also be employed in the system, method and apparatus of the present invention.

 The previous description is of preferred embodiments for
15 implementing the invention, and the scope of the invention should not necessarily be limited by this description. The scope of the present invention is instead defined by the following claims.

WHAT IS CLAIMED IS:

1 1. A communications system for secure wireless
2 communications, said communications system comprising:

3 a first device having transceiving means therein
4 for communicating in a first and a second communication mode;
5 and

6 a second device, in wireless communication with
7 said first device, said first and second devices wirelessly
8 communicating in said first communication mode using an
9 infrared signal and in said second communication mode using
10 a radiofrequency signal.

1 2. The communications system according to claim 1,
2 wherein said first and second devices transceive a plurality
3 of messages therebetween in said second communication mode,
4 wherein, prior to transceiving a security message
5 therebetween, said first and second devices switch
6 transceiving to said first communication mode, and transmit
7 said security message in said first communication mode.

1 3. The communications system according to claim 2,
2 wherein said first and second devices, upon completion of the

3 transceiving of said security message, switch transceiving
4 therebetween to said second communication mode.

1 4. The communications system according to claim 2,
2 wherein said security message comprises a plurality of
3 encryption keys for the subsequent encryption of a plurality
4 of said messages transceived in said second communication
5 mode.

1 5. The communications system according to claim 2,
2 wherein upon said second device switching said transceiving
3 to said first communication mode, said second device
4 transmits an infrared request message to said first device.

1 6. The communication system according to claim 5,
2 wherein said first device, upon receipt of said infrared
3 request message, transmits said security message to said
4 second device.

1 7. The communication system according to claim 6,
2 wherein said security message comprises a plurality of
3 encryption keys for the subsequent encryption of a plurality

4 of said messages transceived in said second communication
5 mode.

1 8. The communication system according to claim 1,
2 wherein said transceiving means within said first device
3 comprises:

4 infrared transceiving means for transceiving
5 infrared signals with said second device in said first
6 communications mode;

7 radiofrequency transceiving means for transceiving
8 radiofrequency signals with said second device in said second
9 communications mode; and

10 switching means for switching between said infrared
11 and radiofrequency transceiving means.

1 9. The communication system according to claim 8,
2 wherein said infrared transceiving means comprises:

3 a photodetector for receiving said infrared signals
4 from said second device; and

5 an infrared emitter for transmitting said infrared
6 signals to said second device.

1 10. The communication system according to claim 1,
2 wherein said second device comprises a transceiving means
3 therein, said transceiving means within said second device
4 comprising:

5 infrared transceiving means for transceiving said
6 infrared signals with said first device in said first
7 communications mode;

8 radiofrequency transceiving means for transceiving
9 said radiofrequency signals with said first device in said
10 second communications mode; and

11 switching means for switching between said infrared
12 and radiofrequency transceiving means.

1 11. The communication system according to claim 10,
2 wherein said infrared transceiving means within said second
3 device comprises:

4 a photodetector for receiving said infrared signals
5 from said first device; and

6 an infrared emitter for transmitting said infrared
7 signals to said first device.

1 12. The communication system according to claim 1,
2 wherein said communication system is a cordless system.

1 13. The communication system according to claim 1,
2 wherein said first and second devices are each selected from
3 the group consisting of:

4 mobile telephones, home base stations, SIM cards,
5 headsets, computers, printers, plotters, projectors,
6 facsimile devices, pagers, data organizers, computer
7 terminals, scanners, microphones, PC cards, televisions,
8 radios, stereos, VCRs, light devices, dimmers, thermostats,
9 doors, refrigerators, freezers, ovens, washers, dryers,
10 answering machines, home alarms, car alarms, and other
11 peripheral and portable devices.

1 14. The communication system according to claim 1,
2 wherein said first and second devices communicate on a
3 radiofrequency band ranging from about 2.4 GHz to about 2.483
4 GHz.

1 15. The communication system according to claim 14,
2 wherein said band is at about 2.45 GHz.

1 16. A method for establishing a secure communication
2 link between a dual-mode first device and a dual-mode second

3 device of a communication system, a first mode of said dual-
4 mode being an infrared mode and a second mode of said dual-
5 mode being a radiofrequency mode, said method comprising the
6 steps of:

7 forwarding an infrared request message in said
8 infrared mode;

9 establishing said secure communication link between
10 said first and second devices, said secure communication link
11 operating in said infrared mode; and

12 transferring, during said secure communications
13 link, a security message between said first and second
14 devices in said infrared mode.

1 17. The method according to claim 16, wherein prior to
2 said establishment of said secure communication link, said
3 first and second devices operated in said radiofrequency
4 mode.

1 18. The method according to claim 16, wherein, in said
2 step of forwarding, said first device forwards said infrared
3 request message to said second device, and said second
4 device, upon receipt of said infrared request message,
5 replies with an infrared reply message.

1 19. The method according to claim 16, wherein said
2 security message comprises a plurality of encryption keys for
3 the subsequent encryption of a plurality of transmissions in
4 said radiofrequency mode.

1 20. The method according to claim 16, further
2 comprising, after said step of transferring said security
3 message, the step of:

4 establishing a radiofrequency communication link
5 between said first and second devices in said radiofrequency
6 mode.

1 21. The method according to claim 16, further
2 comprising, after said step of transferring said security
3 message, the step of:

4 forwarding, from said second device, a security
5 poll signal to said first device.

1 22. The method according to claim 21, wherein said step
2 of forwarding said security poll signal occurs periodically.

1 23. The method according to claim 21, wherein said step
2 of forwarding said security poll signal occurs randomly.

1 24. The method according to claim 16, wherein said
2 first and second devices are each selected from the group
3 consisting of:

4 mobile telephones, home base stations, SIM cards,
5 headsets, computers, printers, plotters, projectors,
6 facsimile devices, pagers, data organizers, computer
7 terminals, scanners, microphones, PC cards, televisions,
8 radios, stereos, VCRs, light devices, dimmers, thermostats,
9 doors, refrigerators, freezers, ovens, washers, dryers,
10 answering machines, home alarms, car alarms, and other
11 peripheral and portable devices.

1 25. The method according to claim 16, wherein said
2 first and second devices communicate on a radiofrequency band
3 ranging from about 2.4 GHz to about 2.483 GHz.

1 26. The method according to claim 25, wherein said band
2 is at about 2.45 GHz.

1 27. A transceiving device for secure wireless
2 communications in a communications system, said device
3 comprising:

4 radiofrequency transceiving means for transceiving
5 a plurality of radiofrequency transmissions within said
6 communications system; and

7 infrared transceiving means for transceiving a
8 plurality of infrared transmissions within said
9 communications system.

1 28. The transceiving device according to claim 27,
2 wherein said infrared transceiving means comprises:

3 a photodetector for receiving said infrared
4 transmissions; and

5 an infrared emitter for transmitting said infrared
6 transmissions.

1 29. The transceiving device according to claim 28,
2 wherein said infrared emitter comprises a light-emitting
3 diode.

1 30. The transceiving device according to claim 27,
2 wherein said transceiving device switches transceiving from

3 said radiofrequency transceiving means to said infrared
4 transceiving means prior to the transmission of an infrared
5 security message within said communications system.

1 31. The transceiving device according to claim 30,
2 wherein, after the transmission of said infrared security
3 message, said transceiving device switches transceiving to
4 said radiofrequency transceiving means.

1 32. The transceiving device according to claim 30,
2 wherein said infrared security transmission comprises a
3 plurality of encryption keys for the subsequent encryption
4 of a plurality of said radiofrequency transmissions between
5 said transceiving device and said communications system.

1 33. The transceiving device according to claim 27,
2 wherein said first and second devices are each selected from
3 the group consisting of:

4 mobile telephones, home base stations, SIM cards,
5 headsets, computers, printers, plotters, projectors,
6 facsimile devices, pagers, data organizers, computer
7 terminals, scanners, microphones, PC cards, televisions,
8 radios, stereos, VCRs, light devices, dimmers, thermostats,

9 doors, refrigerators, freezers, ovens, washers, dryers,
10 answering machines, home alarms, car alarms, and other
11 peripheral and portable devices.

1 34. The Transceiving device according to claim 27,
2 wherein said first and second devices communicate on a
3 radiofrequency band ranging from about 2.4 GHz to about 2.483
4 GHz.

1 35. The transceiving device according to claim 34,
2 wherein said band is at about 2.45 GHz.

ABSTRACT OF THE DISCLOSURE

5 A system, method and apparatus for establishing a
secure wireless radio communications link between two devices
that minimizes the exposure of sensitive information to
third party interception is disclosed. The secure link is
established by first establishing an infrared link between
the two devices for the exchange of sensitive information,
10 such as encryption information. Subsequent communications
would then have the benefit of encryption protection,
establishing the secure wireless radio communications link.




FIG. 2





FIG. 1

**FIG. 3**




FIG. 4

DOCKET NO.: 34650-250

PATENT

COMBINED DECLARATION AND POWER OF ATTORNEY

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name; and

I verily believe that I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled: SYSTEM, METHOD AND APPARATUS FOR SECURE TRANSMISSION OF CONFIDENTIAL INFORMATION, the specification of which:

X is attached hereto.

_____ was filed on _____ under Attorney Docket No. _____ and assigned Application Serial No. _____ and was amended on _____ (if applicable).

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose to the Office all information known to me to be material to the patentability of this application as defined in 37 CFR § 1.56.

I hereby claim foreign priority benefits under 35 U.S.C. § 119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of any application on which priority is claimed:

Country	Number	Date Filed	Priority Claimed
_____	_____	_____	_____
_____	_____	_____	_____

I hereby claim the benefit under 35 U.S.C. § 120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of 35 U.S.C. § 112, I acknowledge the duty to disclose to the Office all information known to me to be material to patentability of the application as defined in 37 CFR § 1.56 which occurred between the filing date of the prior application and the national or PCT international filing date of this application:

Application Serial No.	Filing Date	Status (patented, pending)
------------------------	-------------	----------------------------

--	--	--


I hereby appoint the following attorneys and/or agents to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith: Charles L. Moore, Jr., Reg. No. 33,742; David G. Matthews, Reg. No. 33,959; and Donald D. Mondul, Reg. No. 29957 of ERICSSON INC., 1 Triangle Drive, Research Triangle Park, N.C. 27709, and THOMAS L. CRISMAN, Reg. No. 24,846; THOMAS L. CANTRELL, Reg. No. 20,849; STANLEY R. MOORE, Reg. No. 26,958; H. MATHEWS GARLAND, Reg. No. 19,129; GERALD T. WELCH, Reg. No. 30,332; ROGER L. MAXWELL, Reg. No. 31,855; P. WESTON MUSSELMAN, JR., Reg. No. 31,644; J. KEVIN GRAY, Reg. No. 37,141; JEFFERY E. BACON, Reg. No. 35,055; STEVEN R. GREENFIELD, Reg. No. 38,166; ANDRE M. SZUWALSKI, Reg. No. 35,701; STUART D. DWORK, Reg. No. 31,103; CRAIG A. HOERSTEN, Reg. No. 38,917; ROBERT H. KELLY, Reg. No. 33,922; RICHARD J. MOURA, Reg. No. 34,883; RICHARD L. MYSLIWIEC, Reg. No. 40,098; RAYMOND VAN DYKE, Reg. No. 34,746; BRIAN D. WALKER, Reg. No. 37,751 and KEITH W. SAUNDERS, Reg. No. 41,462 of the firm of JENKENS & GILCHRIST, 3200 Fountain Place, 1445 Ross Avenue, Dallas, Texas 75202-2799; and

Address all telephone calls and correspondence to:


Raymond Van Dyke
Jenkins & Gilchrist, P.C.
3200 Fountain Place
1445 Ross Avenue
Dallas, Texas 75202-2799
214/855-4785

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the

like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

1	PER BJÖRND AHL		1/15/99
	Full Name	Inventor's Signature	Date
	Barkstigen 5, 181 47 Lidingö, SWEDEN	Swedish Citizenship	
	Residence		
	Barkstigen 5, 181 47 Lidingö, SWEDEN		
	Post Office Address		

Correction of home city typing error to Lidingö


1/15/99